

CP70-SL SERIES

Slim Fit Ventilation Fan with Light



Description:

Slim Fit, AC Bathroom Fan. Ceiling or wall mount. Suitable for new construction or remodeling. Fan shall be certified by the Home Ventilating Institute (HVI). 26W compact fluorescent light. ETL/cETL listed for use in insulated ceilings (Type I.C.).

Grille:

Low maintenance, attaches to housing with torsion springs.

Finishes: White (W)

Ventilating Area:

For bathrooms up to 50 square feet.

Motor/Blower:

- Permanently lubricated AC Motor
- Engineered for continuous operation.
- Power rating shall be 120v/60Hz.
- Fan shall be UL and cUL listed for tub/shower enclosure when GFCI protected.
- Motor equipped with thermal shut-off.
- Removal centrifugal type blower wheel assembly.

Warranty:



4 Years when installed by licensed professional.

Architectural Specifications:

Ventilation fan will be ceiling mount, , with no less than 70CFM and no more than 3.6 Sones as certified by HVI at 0.1 static pressure in inches water gauge. Power consumption shall be no greater than 55 watts. The motor will be permanently lubricated and engineered for continuous operation. Uses a 26W compact fluorescent bulb as a light source (not included). Duct diameter will be a 4" round detachable duct. Fan shall be listed for tub/shower enclosure when used with GFCI branch circuit wiring and shall be ETL/cETL listed for use in insulated ceilings (Type I.C.).

Housing:

- Galvanized Steel Body
- 4"round detachable duct connector
- Built-in backdraft damper
- Articulating and expandable anti-vibration brackets included.
- Designed for installation in ceilings with a minimum of 6" clearance.
- May be mounted in sloped ceilings up to 45 degree pitch



Model: CP70-SL Series	4" Duct
Static Pressure (inches w.g.)	0.1
Air Volume (CFM)	70
Noise (Sones)	3.5
Power Consumption (Watts)	55
Current (Amps)	1.2
ENERGY STAR rated	NO
Grille Dimensions	9 1/2" x 8 7/16"

Model	Qty	Comments	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by:
			Date: